



RESOURCE AND PATIENT MANAGEMENT SYSTEM

IHS Pharmacy-Automated Dispensing Interface System (BOP)

Technical Manual

Version 1.0
July 2005
BOP*1.0*1 patch revision

Office of Information Technology Albuquerque, New Mexico

PREFACE

The purpose of this manual is to provide technical information about the IHS Pharmacy-Automated Dispensing Interface System (BOP) package.

TABLE OF CONTENTS

1.0	IN ⁻	TRODUCTION	1
2.0	IM	PLEMENTATION AND MAINTENANCE	2
	2.1 2.2	System Requirements Package-wide Variables	
3.0	RC	OUTINES	3
	3.1 3.2	Routine ListRoutines w/ Descriptions	
4.0	FIL	LES AND TABLES	5
	4.1 4.2 4.3	File ListFile AccessTable File	5
5.0	IN	TERNAL RELATIONS	13
6.0	EX	TERNAL RELATIONS	14
	6.1 6.2 6.3 6.4 6.5	Published Entry Points Exported Options Option List for the BOP User Menu Option List for the BOP IRM Menu Protocol List	14 14 15
7.0	SE	CURITY KEYS	18
8.0	AF	RCHIVING AND PURGING	19
9.0	GE	ENERATING ONLINE DOCUMENTATION	20
	9.1 9.2 9.3 9.4	%INDEXInquire OptionPrint Option FileList File Attributes	21 21
10.0	SA	AC REQUIREMENTS / EXEMPTIONS	23
11.0	GL	_OSSARY	24
12.0	SA	MPLE DATA	27
13.0	CC	ONTACT INFORMATION	32

1.0 Introduction

This manual provides IHS site managers with a technical description of the IHS Interface System routines, files, menus, cross references, globals, and other necessary information required to effectively manage the system.

All routines, files, options, and keys are namespaced starting with the letters 'BOP'. The file number range for this package is 90355 - 90355.44.

2.0 Implementation and Maintenance

2.1 System Requirements

- FileMan v21.0 or higher
- Kernel v8.0 or higher
- PIMS v5.3 or higher
- Inpatient Pharmacy v4.5 or higher
- Outpatient Pharmacy v6.0 or higher
- IHS Third Party Billing System v2.5 or higher

2.2 Package-wide Variables

All package-wide variables in the BOP* routines begin with BOP. All namespaced variables are deleted upon exiting a menu.

3.0 Routines

3.1 Routine List

BOPBAN	BOPEXCP	BOPROC	BOPT3
BOPBAT	BOPINIT	BOPSD	BOPTBS
BOPCAP	BOPKIL	BOPSET	BOPTCP
BOPCLN	BOPMTR	BOPSHO	BOPTD
BOPCP	BOPOBS	BOPSLK	BOPTSD
BOPCP2	BOPRNEW	BOPT1	BOPTU
BOPDRGF	BOPRNEW1	BOPT2	BOPUVER

3.2 Routines w/ Descriptions

Routine	Description
BOPBAN	Displays Package banner on menu
BOPBAT	Batch Automated Dispensing System Messages
BOPCAP	Automated Dispensing System ADT Events &
	Segments: ORC, MSH
BOPCLN	Clean Up Files in 90355.1
BOPCP	Capture and File Data
BOPCP2	Automated Dispensing System Queue Processor
BOPDRGF	Deletion of drugs from 90355.5 file
BOPEXCP	Displays Exception Report
BOPINIT	Pre and Post-init log for package installation
BOPKIL	Purge Queue
BOPMTR	Automated Dispensing System Job Monitor
BOPOBS	Admits, Check OP By Location
BOPRNEW	Automated Dispensing System Listener
BOPRNEW1	Automated Dispensing System Queue Processor
BOPROC	Processes transaction message
BOPSD	Starter Dose logic
BOPSET	Logic for Item index in BOP QUEUE file
BOPSHO	What's in the queue
BOPSLK	Detailed Patient Transaction Display
BOPT1	Automated Dispensing System Send and Receive
BOPT2	Automated Dispensing System Send and Receive
	(Cont)
BOPT3	Transmitter ORC/OBX/RXE/RXR
BOPTBS	Troubleshooting Menu Routine
BOPTCP	TCP/IP Send/Receive Utility
BOPTD	Send Active Inpatients (2)
BOPTSD	Send All Active Inpatients to Interface

Routine	Description
BOPTU	Utility Subroutines
BOPUVER	Logic to create unverified prescription

4.0 Files and Tables

4.1 File List

File Number	File Name
90355	BOP Site
90355.1	BOP Queue
90355.2	BOP Receive Drug
90355.3	BOP Receive Supply
90355.35	BOP IV
90355.4	BOP Receive Exception
90355.44	BOP Transfer to Drug
90355.5	BOP Drug

4.2 File Access

The following table indicates Read, Write, Laygo, Data Dictionary, and Delete access security for all BOP files.

FILE (#)	GL	RD	WR	LYG	DD	DEL
90355	^BOP(90355	<u>a</u>	<u>@</u>	<u>a</u>	(a)	<u>a</u>
90355.1	^BOP(90355.1	@	@	<u>@</u>	<u>@</u>	<u>@</u>
90355.2	^BOP(90355.2	<u>a</u>	<u>@</u>	<u>@</u>	<u>@</u>	<u>a</u>
90355.3	^BOP(90355.3	<u>a</u>	<u>@</u>	<u>@</u>	<u>@</u>	<u>a</u>
90355.35	^BOP(90355.35	<u>a</u>	<u>@</u>	<u>@</u>	<u>@</u>	<u>a</u>
90355.4	^BOP(90355.4	<u>a</u>	<u>@</u>	<u>@</u>	<u>@</u>	<u>a</u>
90355.44	^BOP(90355.44	<u>a</u>	@	<u>a</u>	(a)	<u>@</u>
90355.5	^BOP(90355.5	<u>a</u>	<u>@</u>	<u>@</u>	<u>a</u>	<u>@</u>

4.3 Table File

FILE: BOP SITE GLOBAL: ^BOP(90355, FILE #: 90355

FIELD#	FIELD NAME	SUBSCRIPT	PIECE	TYPE
.01	NAME	D0,0	1	P
.02	FACILITY ID	"	2	F
.03	RECEIVING APPLICATION	"	3	S
.04	ACKNOWLEDGEMENT TIME OUT	"	4	N
.05	NUMBER OF RETRIES	"	5	N
.06	VIEW ALERT MAIL GROUP	"	6	P
.07	SEND PRN	"	7	S
.08	SEND CONTINUOUS	"	8	S
.09	SEND ONE-TIME	"	9	S

FIELD#	FIELD NAME	SUBSCRIPT	PIECE	TYPE
.1	SEND FILL-ON-REQUEST	۲,	10	S
.11	SEND ON-CALL	۲,	11	S
.12	PROCESSING ID	دد	12	S
.13	VERSION ID	دد	13	S
.14	DISPOSITION LOCATION	دد	14	P
1.1	SEND FORMULARY	D0,1	1	S
1.2	ADMIT DIAGNOSIS		2	S
1.3	SEND DISCHARGE ICD9 DIAGNOSIS	دد	3	S
2.1	ADT ACTIVE	D0,2	1	S
2.2	NEW ORDERS ACTIVE	cc	2	S
2.3	RENEW ORDERS ACTIVE	cc	3	S
2.4	OTHER ORDERS ACTIVE	دد	4	S
2.5	INTERFACE VENDOR	cc	5	S
316	ADT SEND OUTPATIENT	دد	6	S
317	ADT SEND INPATIENT	دد	7	S
3	RECEIVING FACILITY (90355.03)			
.01	RECEIVING FACILITY	D0,3,D1,0	1	P
.02	CHANNEL ACTIVE	"	2	S
.03	IP ADDRESS	cc	3	F
.04	SEND SOCKET	cc	4	N
.05	RECEIVE SOCKET	cc	5	N
.06	ACCEPT TRANSACTIONS		6	S
.07	LISTEN CPU		7	F
.08	CLIENT OR SERVER	دد	8	S
.09	PHARMACY OUTPATIENT SITE	cc	9	P
4	MONITOR ACTIVE	D0,4	1	S
4.1	MONITOR RESCHEDULING	ιί	2	N
	FREQUENCY			
4.2	MONITOR CURRENT TASK	cc	3	N
315	BASE ALLERGY	cc	4	P
4.5	DAYS TO KEEP IN QUEUE	cc	5	N
9	P-O INTERFACE DOMAIN	D0,"SITE"	1	F
9.1	LOCATION DECODING TYPE	cc	2	S
9.2	DEFAULT OUTPATIENT LOCATION	cc	3	F
9.3	DEFAULT OP SEND LOCATION	cc	4	F
9.4	SEND ALL OUTPATIENTS	cc	5	S
9.5	DEFAULT OP LOCATION POINTER	cc	6	P
10	OUTPATIENT LOCATION (90355.01)			
.01	OUTPATIENT LOCATION	D0,"OPLOC",D1, 0	1	F
1	OP SEND LOCATION	۲,	2	F
2	OP LOCATION POINTER	۲۲	3	P
12	STOP	D0,12	1	S
401	DEFAULT CLERK	cc	8	P
402	DEFAULT SIG	cc	9	F

FILE: BOP QUEUE GLOBAL: ^BOP(90355.1, FILE #: 90355.1

FIELD#	FIELD NAME	SUBSCRIPT	PIECE	TYPE
.01	DATE/TIME LOGGED	D0,0	1	D

FIELD#	FIELD NAME	SUBSCRIPT	PIECE	TYPE
.02	EVENT TYPE CODE	د د	2	S
.03	DATE/TIME OF EVENT	cc	3	D
.04	MESSAGE TYPE		4	S
.05	DATE/TIME OF MESSAGE	cc	5	D
.06	RECEIVING APPLICATION	دد	6	F
.07	MESSAGE CONTROL ID	cc	7	D
.08	PROCESSING ID	cc	8	S
.09	VERSION ID	cc	9	S
.1	MESSAGE STATUS	cc	10	S
.11	ERROR COUNT	ζζ	11	N
.12	RECEIVING FACILITY	cc	12	P
.21	AO8 ITEM NUMBER	cc	21	N
.41	BCMA STATUS	cc	41	S
.5	FORMULARY	د د	50	S
1.01	PATIENT DFN	D0,1	1	F
1.02	PATIENT ID (INTERNAL ID)	د د	2	F
1.03	PATIENT NAME	دد	3	F
1.04	DATE OF BIRTH	cc	4	D
1.05	SEX	cc	5	S
1.06	RACE	ζζ	6	S
1.07	STREET ADDRESS	ζζ	7	F
1.08	CITY	cc	8	F
1.09	STATE	د د	9	F
1.1	ZIP	cc	10	F
1.11	FACILITY ID	د د	11	F
1.12	PHONE NUMBER – HOME	د د	12	F
1.13	PHONE NUMBER – WORK	cc	13	F
1.14	PATIENT ACCOUNT NUMBER	د د	14	F
1.15	SSN – PATIENT	د د	15	F
2.1	ORDER CONTROL CODE	D0,2	1	S
2.2	PLACER ORDER NUMBER		2	F
2.3	ORDER STATUS	د د	3	S
2.4	POSTING DATE/TIME	cc	4	D
2.5	ENTERED BY	د د	5	F
2.6	VERIFIED BY	د د	6	F
2.7	ORDERING PROVIDER	د د	7	F
2.8	ORDER-DRUG#	، ،	8	F
2.9	IENS (2.5-2.6-2.7)	، ،	9	F
3.1	Q/T FREQUENCY	D0,3	1	F
3.2	Q/T DURATION	"	2	F
3.3	Q/T ORDER START DATE/TIME	cc	3	D
3.4	Q/T ORDER END DATE/TIME	cc	4	D
3.5	Q/T ORDER TYPE	cc	5	S
3.6	Q/T CONDITION PARAMETERS		6	F
3.7	Q/T ADMINISTRATION TIMES	دد	7	F
3.8	IV INFUSION RATE	cc	8	F
3.11	IV ORDER FLAG	cc	11	S
4.01	GIVE CODE IDENTIFIER	D0,4	1	F

FIELD#	FIELD NAME	SUBSCRIPT	PIECE	TYPE
4.02	GIVE CODE TEXT	cc	2	F
4.03	GIVE AMOUNT MINIMUM	cc	3	F
4.04	GIVE AMOUNT MAXIUM	cc	4	F
4.05	GIVE UNIT IDENTIFIER	cc	5	F
4.06	GIVE UNIT TEXT	cc	6	F
4.07	GIVE DOSAGE FORM	cc	7	F
4.08	CONTROLLED SUBSTANCE	cc	8	N
5.1	PROVIDERS ADMIN INSTRUCTIONS	D0,5	1	F
5.2	DISPENSE AMOUNT	cc	2	F
6.1	SPECIAL INSTRUCTIONS	D0,6	1	S
6.2	DISPENSE INSTRUCTIONS	cc	2	F
7.1	GIVE RATE AMOUNT	D0,7	1	F
7.2	GIVE RATE UNIT IDENTIFIER	cc	2	F
7.3	GIVE RATE UNIT TEXT	cc	3	F
7.4	GIVE STRENGTH	cc	4	F
7.5	GIVE STRENGTH UNIT IDENTIFIER	cc	5	F
7.6	GIVE STRENGTH TEXT	cc	6	F
7.7	GIVE INDICATION	cc	7	F
8.1	ROUTE	D0,8	1	F
8.2	DISPENSE CODE		2	S
8.3	CYCLE DATE/TIME	۲,	3	D
8.6	TYPE OF ORDER	cc	6	S
9.1	PATIENT HEIGHT	D0,9	1	N
9.2	PATIENT WEIGHT		2	N
10.1	PATIENT CLASS	D0,10	1	S
10.2	NURSING UNIT		2	F
10.3	ROOM-BED	cc	3	F
10.4	ATTENDING DOCTOR	cc	4	F
10.41	CONSULTING DOCTOR	دد	20	F
10.5	HOSPITAL SERVICE	cc	5	F
10.6	ADMIT DATE/TIME	cc	6	D
10.7	DISCHARGE DATE/TIME	cc	7	D
10.8	ACCOUNT STATUS	cc	8	S
10.9	PRIOR PATIENT ACCOUNT	cc	9	F
	NUMBER			
11	ALLERGY (90355.111)			
.01	ALLERGY	D0,11,D1,0	1	F
.02	ALLERGY INTERNAL NUMBER	cc	2	N
12	ADMIT DIAGNOSIS SHORT	D0,12	1	F
20	SOLUTIONS (90355.12)			
.01	SOLUTIONS	D0,20,D1,0	1	P
20.2	SOLUTION DESCRIPTION	cc	2	F
20.3	SOLUTION VOLUME	cc	3	F
20.11	GLOBAL FOR SOLUTION	cc	11	F
21	ADDITIVE (90355.121)			
.01	ADDITIVE	D0,21,D1,1	1	P
21.2	ADDITIVE DESCRIPTION	cc	2	F
21.3	ADDITIVE STRENGTH	دد	3	F

FIELD#	FIELD NAME	SUBSCRIPT	PIECE	TYPE
21.4	ADDITIVE BOTTLE	cc	4	F
21.11	GLOBAL FOR ADDITIVE	cc	11	F
49.1	DRUG TRANS CODE	D0,49	1	S
49.2	DRUG ID	cc	2	F
50.1	PZFM FORMULARY TRANS CODE	D0,50	1	S
50.2	PZFM MEDICATION ID	دد	2	F
50.3	PZFM GENERIC NAME	66	3	F
50.4	PZFM MEDICATION CLASS	cc	4	F
50.5	PZFM ALTERNATE MED ID	66	5	F
50.6	PZFM FACILITY CODE	cc	6	F
50.7	PZFM BRAND NAME	۲,	7	F
50.8	PZFM DOSAGE FORM	cc	8	F
50.9	PZFM STRENGTH	cc	9	F
50.11	PZFM STRENGTH UNITS	دد	11	F
50.12	PZFM VOLUME	۲,	12	F
50.13	PZFM VOLUME UNITS	۲,	13	F
50.14	PZFM ALTERNATE MED ID2	۲,	14	F
50.15	PZFM THERAPEUTIC CLASS	cc	15	F
50.16	PZFM COST	۲,	16	F
50.17	PZFM CHARGE	cc	17	F
51.1	PZFM MANUFACTURER	D0,51	1	F
51.2	PZFM UNITS OF ISSUE TO MED	· ·	2	F
51.3	PZFM ORDER UNIT FROM SUPPLIER	cc	3	F
51.4	PZFM DISPLAY OPTION	cc	4	F
51.5	PZFM PICK AREA	cc	5	F
51.6	PZFM BILLABLE	cc	6	S
51.7	PZFM MEDICATION NAME	cc	7	F
55.1	OZMI MASTER ITEM FILE ENTRY	D0,55	1	F
55.11	OZMI UNIT OF ISSUE		11	F
55.12	OZMI CONV STOCK TO ISSUE UNIT	cc	12	F
55.13	OZMI NORMAL REORDER SOURCE	cc	13	F
55.14	OZMI NORMAL REORDER BIN LOC	cc	14	F
55.15	OMFE RECORD LEVEL EVENT	cc	15	S
55.16	OZFO NDC	cc	16	F
55.17	OZFO NDC NAME	cc	17	F
55.2	OZMI LOCATION	cc	2	F
55.3	OZMI CHARGE ID	دد	3	F
55.4	OZMI BRAND NAME OF DRUG	cc	4	F
55.5	OZMI PAR LEVEL	cc	5	F
55.6	OZMI PAR LEVEL OZMI REORDER POINT	cc	6	F
55.7	OZMI CRITICALLY LOW LEVEL	cc	7	F
55.8	OZMI QUANITITY ON HAND	cc	8	F
55.9	OZMI UNIT OF RE-STOCK	cc	9	F
56.1	OZMI CRITICAL LOW REORD	DO,56	1	F
30.1	SOURCE SOURCE	DO,30	1	Г
56.2	OZMI CRITI LOW REORD BIN LOC	cc	2	F
56.3	OZMI BILLABLE	cc	3	S
L			1	l

FIELD#	FIELD NAME	SUBSCRIPT	PIECE	TYPE
56.4	OZMI ITEM COST	"	4	F
56.5	OZMI ITEM PRICE	"	5	F
56.6	OZMI UNIT DOSE STRENGTH	"	6	F
56.7	OZMI UNIT DOSE VOLUME	"	7	F
56.8	OZMI TOTAL VOLUME	"	8	F
56.9	OZMI UNIT DOSE DRUG FORM	"	9	F
56.11	OZMI DEA SCHEDULE	"	11	F
56.12	OZMI MANUFACTURER ID/NAME	"	12	F
99	SEND OR FILE	D0,99	1	S
99.1	MED USAGE MESSAGE STATUS	"	2	S
100	DATA (90355.11)			
.01	DATA	D0,"DATA",D1,	1	W
		0		

FILE: BOP RECEIVE DRUG GLOBAL: ^BOP(90355.2, FILE #: 90355.2

FIELD#	FIELD NAME	SUBSCRIPT	PIECE	TYPE
.01	DRUG NAME	D0,0	1	P
.02	PATIENT	"	2	P
.03	DATE VENDED	"	3	D
.04	ORDER NUMBER	"	4	F
.05	QUANTITY VENDED	"	5	N
.06	ORDERED BY	"	6	P
.07	ORDER TYPE	"	7	S
.08	BILLING STATUS	"	8	S
.09	QUEUE #	"	9	P
.1	DISPENSING DEVICE NAME	"	10	F

FILE: BOP RECEIVE SUPPLY GLOBAL: ^BOP(90355.3, FILE #: 90355.3

	TIEE # * VOCCOIC			
FIELD#	FIELD NAME	SUBSCRIPT	PIECE	TYPE
.01	ITEM	D0,0	1	P
.02	PATIENT	دد	2	P
.03	DATE VENDED	دد	3	D
.04	ORDER NUMBER	دد	4	F
.05	QUANTITY VENDED	cc	5	N
.06	ORDERED BY	"	6	P

FILE: BOP IV GLOBAL: ^BOP(90355.35, FILE #: 90355.35

FIELD#	FIELD NAME	SUBSCRIPT	PIECE	TYPE
.01	IV ORDER	D0,0	1	F
.02	PATIENT	"	2	P
.03	DATE VENDED	"	3	D
.04	ORDER NUMBER	"	4	F
.05	TRANSACTION QUANTITY	"	5	N
.08	BILLING STATUS	"	8	S
1	ADDITIVES (90355.351)			

FIELD#	FIELD NAME	SUBSCRIPT	PIECE	TYPE
.01	ADDITIVES	D0,"AD",D1,0	1	P
.02	STRENGTH	۲۲	2	F
.03	BOTTLE	۲۲	3	F
2.01	SOLUTION	D0,"SOL"	1	P
2.02	VOLUME		2	F

FILE: BOP RECEIVE EXCEPTION GLOBAL: ^BOP(90355.4, FILE #: 90355.4

FIELD#	FIELD NAME	SUBSCRIPT	PIECE	TYPE
.01	DATE/TIME OF EXCEPTION	D0,0	1	D
.02	PATIENT	۲۲	2	P
.03	DATE VENDED	۲,	3	D
.04	ORDER NUMBER	۲۲	4	F
.05	TRANSACTION QUANTITY	۲۲	5	N
.06	ORDERED BY	۲,	6	P
.07	ORDER TYPE	۲,	7	S
.08	ORDER NUMBER	۲,	8	F
.09	EXCEPTION TYPE	۲,	9	S
.1	ITEM NAME	۲,	10	F
.11	DRUG	۲,	11	P
.12	CHARGE DESCRIPTION	۲,	12	F
.13	SUB NODE FROM QUEUE FILE	۲,	13	F
5.01	DRUG MEDSTATION	DO,5	1	F
5.02	SUPPLY STATION	٠.	2	F
5.03	VEFS 19235.1 NUMBER	٠.	3	F
5.04	ID NUMBER	٠.	4	N
5.05	PATIENT NAME	دد	5	F

FILE: BOP TRANSFER TO DRUG GLOBAL: ^BOP(90355.44, FILE #: 90355.44

FIELD#	FIELD NAME	SUBSCRIPT	PIECE	TYPE
.01	DATE	D0,0	1	D
.02	DRUG OR SUPPLY	"	2	F
.03	QUEUE FILE ENTRY	"	3	P
.04	PATIENT DFN	"	4	P
.05	PATIENT EXTERNAL NUMBER	"	5	F
.06	PATIENT SSN	"	6	F
.07	DIVISION	"	7	F
.08	PRESCRIPTION	"	8	P
10	PID	D0,1	1	F
20	PV1	D0,2	1	F
30	FT1	D0,3	1	F

FILE: BOP DRUG GLOBAL: ^BOP(90355.5, FILE #: 90355.5

FIELD#	FIELD NAME	SUBSCRIPT	PIECE	TYPE
.01	NAME	D0,0	1	F
2	DRUG ID		2	F

5.0 Internal Relations

The only menu that is intended to be assigned to users is BOPMENU option (BOP User Menu). Users that have this menu option require the security key BOPZMENU.

Within that menu, the user will have access to modify the site parameters, review the records in the queue to be transmitted, transmit data for a single patient, display data that either has been transmitted or will be transmitted for a specific patient, and perform troubleshooting.

There are no options assuming that the entry/exit logic of another option has already occurred.

IRM users are to be assigned the BOP IRM MENU (BOP IRM MENU) option.

6.0 External Relations

In order for outpatient demographic data to be transmitted through the BOP interface, the users must set up specific outpatient locations as they are named in the Hospital Location file (file 40 - ^SC(#)) in the BOP Site File (^BOP(90355)).

Users must either check in a patient or enter in an unscheduled visit through a scheduling option off of the Scheduling or PIMS package menu structure.

- VA Fileman v21.0
- VA Kernel v8.0
- PIMS v5.3
- Inpatient Pharmacy v4.5
- Outpatient Pharmacy v6.0
- IHS 3P Billing System v2.5

6.1 Published Entry Points

Routine	Description
EDIT^BOPCP2	This entry point is called if there is an edit to a
	patient Order.
NEW^BOPCAP	This entry point is called if there is a new order
RENEW^BOPCAP	This entry point is called if an order is
	reactivated
ADT^BOPCAP	[Used as Protocol: "IHS BOP"]
	Capture ADT RPMS events.

6.2 Exported Options

The Interface menus provide control over the interface. Two menus are released with the interface, BOP USER MENU and BOP IRM MENU. The options found on these two menus are listed in the following table.

6.3 Option List for the BOP User Menu

Option Name	Description
BOP DRUG CONFIG	Abbreviation DCF. This menu contains three
	options:
	DFCR – BOP Drug File Contents Report
	RDD – Unverified Rx Drug Delete
	RDE – Unverified Rx Drug Entry
	These options allow the user to manage which

	drugs will result in a prescription being created.	
BOP PATIENT DISPLAY	Abbreviation PAT. This option is used to	
	display the transactions in the sending queue for	
	a particular patient.	
BOP SHOW	Abbreviation: SHOW. This option displays the	
	status of the sending queue. The display shows	
	the total number of items in the queue file, how	
	many are ADT, how many are Orders, and how	
	many timing transactions from Automated	
	Dispensing System	
BOP SITE	Abbreviation: SITE. This option allows the	
	editing of site parameters that control the	
	interface.	
BOP TRANSMIT ONE PATIENT	Abbreviation SEND. This option is often used	
	to force ADT and Order transactions across the	
	interface. If an ADT or order did not make it to	
	the interface, this option allows the sending of	
	all of that patient's current orders to the	
	Automated Dispensing System. The patient IEN	
	(DFN) is entered and if the patient's location is	
	a sending location the patients ADT information	
	and all orders for that patient are sent. This	
	option is for inpatients only.	
BOP TROUBLESHOOT MENU	Abbreviation: TRB. Within this Menu, there	
	are 3 options:	
	CHK Check the Log File	
	FUT Display Future Monitor tasks	
	RUN Display Running Tasks and job ID	
	There are times when the interface will have	
	nothing to send. At that time, it will create a	
	future BOP Monitor task scheduled for 3 to 15	
	minutes in the future. If you see a Future Task,	
	it means the interface is running, but completed its processing and will check for more	
	processing and will check for more processing at the time listed in TaskMan.	
	The CHK option will show the actual numbers	
	in the Queue file that are waiting to be sent. If	
	there are entries in that file and the numbers do	
	not change, contact IRM and let them know.	
	not onango, contact new and let them know.	

6.4 Option List for the BOP IRM Menu

Option Name	Description
BOP MONITOR Abbreviation MON. This option starts the	
	interface monitor. The monitor constantly
	checks the system to see if the appropriate jobs

	are running. If it finds that a necessary process
	is not running, it schedules it to run using the
	RPMS Task Manager. The monitor process
	reschedules itself using the RPMS background
	task scheduler, TaskMan. It will run 'X' seconds
	in the future, (determined by the field
	"Reschedule Frequency" in the IHS BOP Site
	Parameters file, #90355 – Recommend 300 to
	900 seconds). When it runs it checks to see if
	the transmitter to Automated Dispensing
	System and receiver from Automated
	Dispensing System are running and attempts to
	start them if they are not running.
BOP PATIENT DISPLAY	Abbreviation PAT. This option is used to
	display the transactions in the sending queue for
	a particular patient.
BOP SHOW	
BOF SHOW	Abbreviation: SHOW. This option displays the
	status of the sending queue. The display shows
	the total number of items in the queue file, how
	many are ADT, how many are Orders, and how
	many timing transactions from Automated
	Dispensing System
BOP SITE	Abbreviation: SITE. This option allows the
	editing of site parameters that control the
	interface.
BOP STOP	Abbreviation: STOP. The interface can be
	stopped in two ways. The first is to edit the
	setup file and change the monitor active field
	(file 90355) from ON to OFF. This will stop the
	monitor so that the monitor will not reschedule
	itself in TaskMan. This does not stop the current
	running transmitter or receiver. The second way
	to stop the interface is to use this option. This
	option will halt the current running transmitter
	and receiver but does not interfere with the
	interface monitor. Use this option if the
	interface needs to be stopped for a short while
	but not permanently.
BOP TRANSMIT ONE PATIENT	Abbreviation SEND. This option is often used
	to force ADT and Order transactions across the
	interface. If an ADT or order did not make it to
	the interface, this option allows the sending of
	all of that patient's current orders to the
	Automated Dispensing System. The patient IEN
	(DFN) is entered and if the patient's location is a sending location the patients ADT information

	and all orders for that patient are sent. This option is for inpatients only.
BOP TROUBLESHOOT MENU	Abbreviation: TRB. Within this Menu, there
	are 3 options:
	CHK Check the Log File
	FUT Display Future Monitor tasks
	RUN Display Running Tasks and job ID
	There are times when the interface will have
	nothing to send. At that time, it will create a
	future BOP Monitor task scheduled for 3 to 15
	minutes in the future. If you see a Future Task,
	it means the interface is running, but completed
	its processing and will check for more
	processing at the time listed in TaskMan.
	The CHK option will show the actual numbers
	in the Queue file that are waiting to be sent. If
	there are entries in that file and the numbers do
	not change, contact IRM and let them know.

6.5 Protocol List

Protocol	Description
BOP DG ADT	BOP Inpatient ADT Event Protocol – Attaches to
	BDGPM MOVEMENT EVENTS extended
	action protocol
BOP GMRA	BOP Update Allergy – Attaches to GMRA
UPDATE	VERIFY DATA extended action protocol.
BOP SDAM	BOP Outpatient ADT Event Protocol – Attaches
	to BSDAM APPOINTMENT EVENTS extended
	action protocol.

7.0 Security Keys

The security keys BOPZIRM and BOPZMENU have been released with the KIDS package. These keys should be assigned to the users who will have the BOP IRM MENU or BOP USER MENU.

8.0 Archiving and Purging

The Automated Dispensing System removes old data from the BOP QUEUE file on a regular basis. The purge logic uses the value set in the DAYS TO KEEP IN QUEUE field in the BOP SITE file to determine how many days of data remain in the Queue. If a value hasn't been defined, a default of 7 days is used.

9.0 Generating Online Documentation

This section describes a few methods to generate Patient Registration system technical documentation. Online BOP technical documentation, in addition to that which is located in the help prompts throughout the Patient Registration package, can be generated through the use of several Kernel options. These include, but are not limited to, the following:

- %INDEX
- Menu Management
- Inquire Option
- Print Option File
- VA FileMan
- Data Dictionary Utilities
- List File Attributes

Typing? at the "Select . . . Option" prompt will provide online technical information.

- A single question mark (?) lists all options that can be accessed from the current option.
- Two question marks (??) list all options accessible from the current one, showing the formal name and lock for each.
- Three question marks (???) display a brief description for each option in a menu.
- An option name preceded by a question mark (?OPTION) shows extended help, if available, for that option.

For a more exhaustive option listing and further information about other utilities that supply online technical information, consult the DHCP Kernel Reference manual.

9.1 %INDEX

This option analyzes the structure of a routine to determine in part if the routine adheres to RPMS programming standards. The %INDEX output can include the following components:

- Compiled list of errors and warnings
- Routine listing
- Local variables
- Global variables
- Naked globals
- Label references
- External references

Running %INDEX for a specified set of routines, allows users to discover any deviations from RPMS programming standards that exist in the selected routines and

to see how routines interact with one another (i.e., which routines call or are called by other routines).

To run %INDEX for the BOP package, type the BOP namespace at the Routine(s)?> prompt.

9.2 Inquire Option

This menu management option provides the following information about a specified option:

- Option name
- Menu text
- Option description
- Type of option
- Lock (if any)

In addition, all items on the menu are listed for each menu option. To secure information about patient registration options, specify the BOP namespace.

9.3 Print Option File

This utility generates a listing of options from the Option file (#19). Users can choose to print all of the entries in this file or specify a single option or range of options. For a list of BOP options, refer to the Exported Options section of this manual.

9.4 List File Attributes

This VA FileMan option allows users to generate documentation pertaining to files and file structure. Using the standard format of this option yields the following data dictionary information for a specified file:

- File name and description
- Identifiers
- Cross-references
- Files pointed to by the file specified
- Files that point to the file specified
- Input, print, and sort templates

In addition, the following applicable data is supplied for each field in the file:

- Field name, number, title, and description
- Global location
- · Help prompt
- Cross-references
- Input transform

- Date last edited
- Notes

Using the Global Map format of this option generates an output that lists the following information:

- All cross-references for the file selected
- Global location of each field in the file
- Input, print, and sort templates

For a comprehensive listing of BOP package files, please refer to the Files section of this manual (section 4.0).

10.0 SAC Requirements / Exemptions

Exemptions to allow references to \$ETRAP were approved on March 16, 2005.

Request exemption for # reads. These are necessary for interactive interface processing. # reads appropriately check for the carriage return/line feed at the segment ends of the HL7 messages.

11.0 Glossary

Archiving The storing of historical or little-used data off-line (often on

tape).

ASUFAC number

Area Service Unit Facility; A unique identifier for each facility within IHS. A six-digit number comprised of 2 digits for Area,

2 digits for Service Unit, and 2 digits for Facility.

Banner A line of text with a user's name and domain.

Browser An interactive application that displays ASCII text on a terminal

that supports a scroll region. The text can be in the form of a word-processing field or sequential local or global array. The

user is allowed to navigate freely within the document.

Callable Entry

Points

Places in a routine that can be called from an application

program.

Cross-reference An indexing method whereby files can include pre-sorted lists of

entries as part of the stored database. Cross-references (x-refs)

facilitate look-up and reporting.

Default Facility A user selects a facility identification to work with patients

registered to that facility.

Entry Point Entry point within a routine that is referenced by a "DO" or

"GOTO" command from a routine internal to a package.

File A set of related records or entries treated as a single unit.

FileMan The database management system for RPMS.

Global In MUMPS, global refers to a variable stored on disk (global

variable) or the array to which the global variable may belong

(global array).

Health Record

Number (HRN)

Each facility assigns a unique number within that facility to each patient. Each HRN with its facility identification 'ASUFAC'

make a unique identifier within all of IHS.

INDEX

(%INDEX) as

A Kernel utility used to verify routines and other MUMPS code associated with a package. Checking is done according to

current ANSI MUMPS standards and RPMS programming standards. This tool can be invoked through an option or from

direct mode (>D ^%INDEX).

Init Initialization of an application package. The initialization step in

the installation process builds files from a set of routines (the init

routines). Init is a shortened form of initialization.

Internal Entry Number (IEN) The number used to identify an entry within a file. Every record

has a unique internal entry number.

IRM Information Resource Management. The IHS personnel

responsible for information systems management and security.

Kernel The set of MUMPS software utilities that function as an

intermediary between the host operating system and application

packages, such as Laboratory and Pharmacy. The Kernel provides a standard and consistent user and programmer interface between application packages and the underlying MUMPS implementation. These utilities provide the foundation

for RPMS.

Menu A list of choices for computing activity. A menu is a type of

option designed to identify a series of items (other options) for presentation to the user for selection. When displayed, menutype options are preceded by the word "Select" and followed by the word "option" as in Select Menu Management option: (the

menu's select prompt).

Namespace A unique set of 2 to 4 alpha characters that are assigned by the

database administrator to a software application.

Official Registering Facility

A facility so designated that when HRNs are added/modified, those changes are sent to the central database. A Service Unit may have several satellites for which it is registering patients.

Option An entry in the Option file. As an item on a menu, an option

provides an opportunity for users to select it, thereby invoking the associated computing activity. Options may also be scheduled to run in the background, non-interactively, by

TaskMan.

Patient Care Component (PCC) The central repository for data in the Resource and Patient

Management System (RPMS).

Queuing Requesting that a job be processed at a later time rather than

within the current session.

Routine A program or sequence of instructions called by a program that

may have some general or frequent use. MUMPS routines are groups of program lines that are saved, loaded, and called as a

single unit via a specific name.

UCI User Class Identification: a computing area.

Up-Hat (^) A circumflex, also know as a "hat" or "caret," that is used as a

piece delimiter in a global. The up-hat is denoted as "^" and is

typed by pressing Shift+6 on the keyboard.

Utility A callable routine line tag or function. A universal routine usable

by anyone.

Variable A character or group of characters that refers to a value.

MUMPS recognizes 3 types of variables: local variables, global variables, and special variables. Local variables exist in a partition of the main memory and disappear at sign-off. A global variable is stored on disk, potentially available to any user.

Global variables usually exist as parts of global arrays.

12.0 Sample Data

RECORD LINKAGE for BOP INTERFACE:

90355.1 NEW ADT – ADMISSION INTO EMERGENCY ROOM:

```
NUMBER: 201
                                       DATE/TIME LOGGED: FEB 13,
2004@11:02:31
 EVENT TYPE CODE: A01
                                       DATE/TIME OF EVENT: 1730
 MESSAGE TYPE: ADT
 DATE/TIME OF MESSAGE: FEB 13, 2004@11:02:31
 RECEIVING APPLICATION: OMNICELL
 MESSAGE CONTROL ID: FEB 13, 2004@11:02:31
 PROCESSING ID: P
                                       VERSION ID: 2.2
 MESSAGE STATUS: Closed
 RECEIVING FACILITY: CLAREMORE INDIAN HOSPITAL
 PATIENT DFN: 8570
                                       PATIENT ID (INTERNAL ID): 8570
                                       DATE OF BIRTH: JAN 14, 1939
 PATIENT NAME: PATIENT, DEMO
                                      STREET ADDRESS: RT. 1 BOX 99-3
 SEX: M
 CITY: DEMO
                                    STATE: OKLAHOMA
 ZIP: 74016
                                      FACILITY ID: 505201
 PHONE NUMBER - HOME: 999-3894
                                      PATIENT ACCOUNT NUMBER: 7856993
 SSN - PATIENT: 000330000
                                      PATIENT CLASS: O
 NURSING UNIT: EMERGENCY MED
```

Actual Global for record 201:

DRUG INFO BACK INTO RPMS: 90355.1 DRUG RECORD

Actual global info for record number 280183:

```
^BOP(90355.1,280183,0)=3060410.100209^^^^^^99^^1
                   99) = 1^9
^BOP(90355.1,280183,"DATA",0)=^^5^5^3060410
^BOP(90355.1,280183,"DATA",1,0)=MSH|^~\&|PYXIS|PYXISPH|RPMS|BILLFAC|200604101
004
28||DFT^P03|EVM^04102006100428|P|2.3|||||
^BOP(90355.1,280183,"DATA",2,0)=PID|||||STAR^DEMO||||||||||||178387||
^BOP(90355.1,280183,"DATA",3,0)=PV1|||ED^^^||||||||||||||0|
^BOP(90355.1,280183,"DATA",4,0)=FT1||||200604101003||V|441^hydrOXYzine
INJ|||1||
||||D|||MDA18^ CLERK, First |^||
^BOP(90355.1,280183,"DATA",5,0)=ZPM|V|console|ED-MAIN|8|A2|441|hydrOXYzine
|11|11|1|MDA18| CLERK, First |D||10|00517-5601-
25|||ED|1|12|5|20060410100335|||
^BOP(90355.1,280183,"OUT",0)=60365,36129
                          1)=
     MSH|^~\&|PYXIS|PYXISPH|RPMS|BILLFAC|20060410100428|
      |ACK|EVM^04102006100428|P|2.3|||||
                           2) =MSA | AA | 280183 |
```

90355.44 RECORD FOR DRUG:

```
DATE: MAR 22, 2006@05:04:12 DRUG OR SUPPLY: D
QUEUE FILE ENTRY: 256277 PATIENT DFN: STAR, DEMO
PATIENT EXTERNAL NUMBER: 269809 PRESCRIPTION: 3973015
PID: PID|||203951||STAR PV1: PV1|||ER
FT1: FT1||||20060322||V|6307
```

Actual global entry for record number 340:

IHS HL7 SUPPLY FILE ENTRY FOR DRUG:

```
^AUPNSUP(204759,0)=MORPHINE INJ^176686^3060409.12^^3060410.0919
1)=85552
2)=MORPHINE INJ^3060409.12^1^1.130
```

SUPPLY RECORD

```
90355.1 RECORD:

SUPPLY NAME: MORPHINE INJ
DATE ISSUED: APR 09, 2006@12:00

TRANSACTION CODE: 85552
CHARGE DATE: APR 09, 2006@12:00

UNIT PRICE: 1.130

PATIENT NAME: STAR, DEMO
DATE OF DATA ENTRY: APR 10,

SUPPLY DESCRIPTION: MORPHINE INJ
QUANTITY: 1
```

Example of processing supply items using Third Party Billing

```
EDTP Add/Edit Claim Menu ...
 MGTP Claim/Bill Management Menu ...
 RPTP Reports Menu ...
  PRTP Print Bills Menu ...
      Table Maintenance Menu ...
  TMTP
  ELTP Eligibility Reports Menu ...
  PPTP Payment Posting
 EMTP Electronic Media Claims ...
  SSTP Set Site
Select Third Party Billing System Option: ED Add/Edit Claim Menu
        THIRD PARTY BILLING SYSTEM - VER 2.5
                     Add/Edit Claim Menu
                      CLAREMORE HOSPITAL
        User: USER, A
                                13-FEB-2004 2:28 PM
  CG1P Claim Generator, One Patient
 EDCL Edit Claim Data
  LOOP Claim Editor Loop
  NEW Add New Claim (Manual Entry)
  RBCL Rebuild Items from PCC
Select Add/Edit Claim Menu Option: ED Edit Claim Data
        THIRD PARTY BILLING SYSTEM - VER 2.5
                      Edit Claim Data
                      DEMO HOSPITAL
        User: USER, A
                               13-FEB-2004 2:28 PM
Select CLAIM or PATIENT: OMNICELL, TEST
                             M 05-05-1955 099999999 CL 898989
PATIENT: OMNICELL, TEST M 05/05/1955 099-99-9999 HRN: 898989
______
(1) Claim# 597144 02/13/2004 OUTPATIENT EMERGENCY MEDICINE DEMO MAIL HANDLERS BENEFIT/FL Status: In EDIT Mode
Select 1 to 1: 1
           ...< Processing, Claim Error Checks >>...
```

```
...< Checking Eligibility Files for Potential Coverage >>...
There are SUPPLIES/MEDS on file that may need to be added to this claim.
PATIENT: OMNICELL, TEST VISIT DATE: FEB 13,2004 TO: FEB 13,2004
Beginning Date for Supply/Med Charges: FEB 13,2004//
Ending Date for Supply/Med Charges: FEB 13,2004//
Supply Charges
                Feb 13, 2004 14:28:38 Page: 1 of
              3P NUM: 597144
              PATIENT: OMNICELL, TEST
      ADMIT/VISIT FROM: FEB 13,2004 TO: FEB 13,2004
                                  TRANCODE/ REV/
SUPPLY/MED NAME
                         QUAN PRICE NDC HCPC DEPT CLAIM NO.
                            1 1.55 00026-8841-48
1 NIFEDIPINE ER
  FEB 12,2004@13:49:51
2 IBUPROFEN
                           1 0.29 49884-0469-01
 FEB 12,2004@13:50:01
3 TUBE, SUCT. SURG. SALEM 1.2M 1 0.00 A7002
 FEB 12,2004@13:50:14
```

13.0 Contact Information

If you have any questions or comments regarding this distribution, please contact the OIT Help Desk by:

Phone: (505) 248-4371 or

(888) 830-7280

Fax: (505) 248-4363

Web: http://www.rpms.ihs.gov/TechSupp.asp

Email: <u>ITSCHelp@mail.ihs.gov</u>